

Model Shown:
PTPHD-110



Features

5 TO 50-TON CAPACITY HYDRAULIC PULLERS KITS ARE AVAILABLE IN 2- OR 3-JAW MODELS AND OFFER MANY OPTIONS FOR FLEXIBILITY WITH ANY PROJECT.

- 5 to 50-ton capacity puller with up to 14" (356 mm) reach and 25" (635 mm) spread for large pulling requirements
- Lightweight, industry leading 10,000 PSI (690 Bar) heavy-duty electric pump for reliable performance use after use
- 10,000 PSI (690 Bar) single-acting cylinder that allows for high tonnage repeatable execution
- 25 and 50-ton pullers include a storage cart for ease of transportation to and from the job site



Included with the Kits*

- Puller Iron and Ram Point Set
- Hydraulic Cylinder
- Lift and Positioning Plate
- 2 Stage Electric Pump
- Gauge Adapter, 10,000 PSI (690 Bar) Gauge
- 10' heavy-duty Hydraulic Hose
- Male Coupler with dust cap

* PTPHC and PTPHD Hydraulic puller sets with 25-ton and 50-ton capacities include the PTPT-2550 storage cart.



Ordering Information

2 Jaw		3 Jaw		Optional Accessories				
Order No.	Order No.	Cap. Short Tons	Cylinder Included	Reach	Spread	Long Jaws*		
				in. (mm)	in. (mm)	Order No.	Reach in. (mm)	Spread in. (mm)
PTPHD-206	PTPHD-106	5	C55C	6 (152)	.5 to 8 (13 to 203)	-	-	-
PTPHD-208	PTPHD-108	10	C106C	8 (203)	.75 to 12 (19 to 305)	PT11054 PT11054L	9.8 (249) 16 (406)	15.8 (401) 22 (559)
PTPHD-210	PTPHD-110	15	C1510C	9.67 (245)	1 to 15 (25 to 38)	PTPH-11054L	16 (406)	22 (559)
PTPHD-213	PTPHD-113	25	C2514C	12 (305)	2.5 to 18 (64 to 457)	PT11354L	20 (508)	30 (762)
---	PTPHD-116	50	C5513C	14 (356)	3 to 25 (76 to 635)	PTPH-21654L	26 (660)	38 (965)



* Long jaws must be ordered in the quantity required. For example, order three PT11054 for the PTPHD-108.

Model Shown:
PTPHC-110



Features

THESE HYDRAULIC PULLERS DESIGNED TO HANDLE REMOVING JOBS WITH A MINIMAL AMOUNT OF EFFORT FOR THE ULTIMATE EFFICIENT PULLING SOLUTION.

- 5 to 50-ton capacity puller with up to 14" (356 mm) reach and 25" (635 mm) spread for large pulling requirements
- Lightweight, two-speed manually operated 10,000 PSI (690 Bar) hydraulic pump provides high oil volume for fast cylinder piston approach, then the pump automatically shifts to the high-pressure stage to move the load
- 10,000 PSI (690 Bar) single-acting cylinder that allows for high tonnage repeatable execution
- 25 and 50-ton pullers include a storage cart for ease of transportation to and from the job site



Included with the Kits*

- Puller Iron and Ram Point Set
- Hydraulic Cylinder
- Lift and Positioning Plate
- Two Speed Manually operated Pump
- Gauge Adapter, 10,000 PSI (690 Bar) Gauge
- 10' (3.05 m) heavy-duty Hose
- Male Coupler with dust cap

* PTPHC and PTPHD Hydraulic puller sets with 25-ton and 50-ton capacities include the PTPT-2550 storage cart.



Ordering Information

2 Jaw		3 Jaw									Optional Accessories		
Order No.	Order No.	Cap. Short Tons	Cylinder Included	Pump Included	Gauge Included	Hose Included	T Adapter Included	Reach in. (mm)	Spread in. (mm)	Long Jaws*			
Order No.	Order No.	Cap. Short Tons	Cylinder Included	Pump Included	Gauge Included	Hose Included	T Adapter Included	Reach in. (mm)	Spread in. (mm)	Order No.	Reach In. (mm)	Spread In. (mm)	
PTPHC-206	PTPHC-106	5	C55C	P19L	9040	9756	9670	6 (152)	.5 to 8 (13 to 203)	-	-	-	
PTPHC-208	PTPHC-108	10	C106C	P19L	9040	9756	9670	8 (203)	.75 to 12 (19 to 305)	PT11054 PT11054L	9.8 (249) 16 (406)	15.8 (401) 22 (559)	
PTPHC-210	PTPHC-110	15	C1510C	P59L	9040	9756	9670	9.67 (245)	1 to 15 (25 to 38)	PTPH-11054L	16 (406)	22 (559)	
PTPHC-213	PTPHC-113	25	C2514C	P159	9040	9756	9670	12 (305)	2.5 to 18 (64 to 457)	PT11354L	20 (508)	30 (762)	
---	PTPHC-116	50	C5513C	P460	9040	9756	9670	14 (356)	3 to 25 (76 to 635)	PTPH-21654L	26 (660)	38 (965)	



* Long jaws must be ordered in the quantity required. For example, order three PT11054 for the PTPHC-108.

Model Shown:
PTPHB-116, PTPHB-110



Features

KNOWN FOR SAFETY, DURABILITY, AND EASE OF USE, POSI LOCK PULLERS ARE DESIGNED TO HELP EXTEND BEARING LIFE IN APPLICATIONS THROUGH PROPER INSTALLATION, REMOVAL, AND SERVICE.

- 5 to 50-ton capacity puller with up to 14" (356 mm) reach and 25" (635 mm) spread for large pulling requirements
- 10,000 PSI (690 Bar) single-acting cylinder that allows for high tonnage repeatable execution
- 25 and 50-ton pullers include a storage cart for ease of transportation to and from the job site
- Slim tapered heat-treated tips allow for better gripping and easier access in tight spots



Puller Accessories

Power Team offers accessories to compliment your puller. These accessories conveniently store, transport and position your hydraulic pullers to maximize your productivity.



Order No.	Puller No. *
Storage Transport Cart	
PTPT-2550	PTPHB-213
PTPT-2550	PTPHB-113
PTPT-2550	PTPHB-116

Ordering Information

2 Jaw	3 Jaw	Cap. Short Tons	Cylinder Included	Reach	Spread	Order No.	Reach	Spread
Order No.	Order No.			in. (mm)	in. (mm)		in. (mm)	in. (mm)
PTPHB-206	PTPHB-106	5	C55C	6 (152)	.5 to 8 (13 to 203)	-	-	-
PTPHB-208	PTPHB-108	10	C106C	8 (203)	.75 to 12 (19 to 305)	PT11054 PT11054L	9.8 (249) 16 (406)	15.8 (401) 22 (559)
PTPHB-210	PTPHB-110	15	C1510C	9.67 (245)	1 to 15 (25 to 38)	PTPH-11054L	16 (406)	22 (559)
PTPHB-213	PTPHB-113	25	C2514C	12 (305)	2.5 to 18 (64 to 457)	PT11354L	20 (508)	30 (762)
---	PTPHB-116	50	C5513C	14 (356)	3 to 25 (76 to 635)	PTPH-21654L	26 (660)	38 (965)



Optional Accessories

Long Jaws*

* Long jaws must be ordered in the quantity required. For example, order three PT11054 for the PTPHB-108.

Model Shown:

PTPH-113IE (Internal/External)



Features

INTERNAL/EXTERNAL PULLING MADE EASY. FUNCTIONS WITH A PTPHB, PTPHC, AND PTPHD HYDRAULIC 5 TO 50-TON CAPACITY PULLERS TO ALLOW THE FLEXIBILITY OF INTERNAL OR EXTERNAL PULLING.

- External pulling up to 20" (508 mm) reach and 30" (762 mm) spread for large pulling requirements
- Internal pulling up to 7" (178 mm) reach and 21" (533 mm) spread for an effective range of internal pulling capabilities
- Safety cage houses either the internal or external jaws by simply removing the ball lock pins that allows you to change from internal to external in seconds
- Slim tapered heat-treated tips permit better gripping and easier access in tight spots

Ordering Information

Order No.	Number of Jaws	Part Number	Jaw Style	Reach In. (mm)	Spread In. (mm)	Overall Length In. (mm)	Jaw Width In. (mm)	Jaw Length In. (mm)
PTPH-113IE	3	11354T	Internal	7 (178)	8 to 21 (203 to 533)	25.75 (654)	1.25 (32)	10.9 (277)
	3	11354	External	12 (305)	2.5 to 18 (64 to 457)	27 (686)	1.25 (32)	13.7 (348)
OPTIONAL	3	11354L	External Long	20 (508)	1.5 to 30 (38 to 762)	36 (914)	1.25 (32)	21.6 (549)